



**REQUEST OF QUOTATION - OPEN CIRCUIT COOLING TOWER**

Date \_\_\_\_\_

Project name\* \_\_\_\_\_

Company \_\_\_\_\_

Reference person \_\_\_\_\_

Telephone \_\_\_\_\_ Fax \_\_\_\_\_ E-Mail \_\_\_\_\_ Web site \_\_\_\_\_

Customer  User  Installer  Other  
 Machine Manufacturer  Engineering company (designer)

Request  Offer  Budget  Offer for Engineering/Design  
 Other  Final Offer

**Selection data \***

Thermal Capacity kW \_\_\_\_\_  
kcal/h \_\_\_\_\_

Water flow m<sup>3</sup>/h \_\_\_\_\_

Water inlet temperature °C \_\_\_\_\_

Water outlet temperature °C \_\_\_\_\_

Wet bulb temperature °C \_\_\_\_\_

Installation town \_\_\_\_\_

Cooling tower type  with water collecting basin  if without basin, specify:  
 without water collecting basin  with supporting frame (lower structure with air inlet louvers)

Field of application  HVAC  Industry (specify type of Industry \_\_\_\_\_)

Type of equipment connected to the cooling tower \_\_\_\_\_  
 Process involves power peaks that could significantly vary water inlet temperature

Water quality \*  Very clean (fill pack 12 mm. Film type)  Water with low quantity of suspended particles  
 Industrially clean (fill pack 19 mm. Film type)  Water with high quantity of suspended particles (fill pack splash type)  
 Acid  Demineralised water, aggressive water

Please share complete water analysis and our consultants will select the best construction materials for your cooling tower

Type of cooling  Direct  Indirect (Heat-exchanger, Chiller)  
If chiller:  specify if "absorption chiller"

Version  Standard  Low ambient temperature  Silent (indicate max db(A) allowed)  
 Metal parts in SS (instead of standard HDGS)  If metal parts in stainless steel: SS 304  Special Version "CONTAINER" (dimension suitable for shipment in Container)  
 If metal parts in stainless steel: SS 316

Use  Normal (working days)  Seasonal  
 24 h/day

Plant  New  Replacement (specify model and brand to be replaced \_\_\_\_\_)

Maximum footprint m x m \_\_\_\_\_

Optionals/ Accessories  Silencers  PTC  External fan heater  
 Safety ladder + handrail  Inverter system "MCS Control Panel"  Vibraswitch  
 Removable wall  Fill pack in PP  Water distribution in Polyethylene  
 Basin heater  Water distribution in PP  Anticondensation heater for Motor  
 Low level switch  Water treatment "MITA Systems" (please send us the water analysis)  SILENT(indicate max db(A) allowed)

Additional notes: \_\_\_\_\_

Deadline: \_\_\_\_\_

Please send this format by fax to +39 0382 617640 or by e-mail to [export@mitact.it](mailto:export@mitact.it)

\*Mandatory fields